

1 Identification of substance

- **Product details**
- **Trade name:** 39854 Texture Coating
- **Article number:** 39854
- **Manufacturer/Supplier:**
SEM Products, Inc.
651 Michael Wylie Dr.
Charlotte, NC 28217
USA
(704)522-1006
- **Information department:** 24HR EMERGENCY CHEMTREC 800-424-9300

2 Composition/Data on components

- **Chemical characterization**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

108-88-3	toluene	25-50%
14808-60-7	Quartz (SiO ₂)	10-25%
	ACRYLIC RESIN	10-25%
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	10-25%
78-93-3	butanone	2.5-10%
108-65-6	2-methoxy-1-methylethyl acetate	2.5-10%
67-56-1	methanol	≤ 2.5%

3 Hazards identification

- **Hazard description:**



Toxic
Highly flammable

- **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.

May cause cancer by inhalation.

Highly flammable.

Harmful by inhalation.

Irritating to eyes, respiratory system and skin.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Harmful: possible risk of irreversible effects through inhalation.

Possible risk of harm to the unborn child.

Harmful: may cause lung damage if swallowed.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

(Contd. on page 2)

USA

Printing date 06/03/2005

Reviewed on 12/21/2004

Trade name: 39854 Texture Coating

(Contd. of page 1)

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



4 First aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

5 Fire fighting measures

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.

· **Measures for environmental protection:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Measures for cleaning/collecting:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

7 Handling and storage

· **Handling:**

· **Information for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

(Contd. on page 3)



Trade name: 39854 Texture Coating

(Contd. of page 2)

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls and personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

108-88-3 toluene

PEL Short-term value: C 300; 500* ppm

Long-term value: 200 ppm

*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

TLV 188 mg/m³, 50 ppm

Skin; BEI

14808-60-7 Quartz (SiO₂)

REL 0.05* mg/m³

*Respirable dust

TLV (0.05 R) mg/m³

NIC-0.025 R

78-93-3 butanone

PEL 590 mg/m³, 200 ppm

REL Short-term value: 885 mg/m³, 300 ppm

Long-term value: 590 mg/m³, 200 ppm

TLV Short-term value: 885 mg/m³, 300 ppm

Long-term value: 590 mg/m³, 200 ppm

BEI

67-56-1 methanol

PEL 260 mg/m³, 200 ppm

REL Short-term value: 325 mg/m³, 250 ppm

Long-term value: 260 mg/m³, 200 ppm

Skin

TLV Short-term value: 328 mg/m³, 250 ppm

Long-term value: 262 mg/m³, 200 ppm

Skin; BEI

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

(Contd. on page 4)



Trade name: 39854 Texture Coating

(Contd. of page 3)

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 79°C (174°F)

· **Flash point:** -4°C (25°F)

· **Ignition temperature:** 315.0°C (599°F)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower: 1.2 Vol %

Upper: 7.0 Vol %

· **Vapor pressure at 20°C (68°F):** 29.0 hPa (22 mm Hg)

· **Density at 20°C (68°F):** 1.18 g/cm³

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

(Contd. on page 5)

Material Safety Data Sheet

acc. to ISO/DIS 11014



Printing date 06/03/2005

Reviewed on 12/21/2004

Trade name: 39854 Texture Coating

(Contd. of page 4)

- **Solvent content:**
 - Organic solvents:** 50.6 %
 - VOC content:** 50.6 %
 - 600.8 g/l / 5.01 lb/gl
- **Solids content:** 49.3 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

Carcinogenic if inhaled.

12 Ecological information

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **Product:**
- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

USA

(Contd. on page 6)

Printing date 06/03/2005

Reviewed on 12/21/2004

Trade name: 39854 Texture Coating

(Contd. of page 5)

14 Transport information

· DOT regulations:



- Hazard class: 3
- Identification number: UN1263
- Packing group: II
- Proper shipping name (technical name): PAINT
- Label: 3

· Land transport ADR/RID (cross-border):



- ADR/RID class: 3 Flammable liquids
- Danger code (Kemler): 33
- UN-Number: 1263
- Packaging group: II
- Label: 3
- Description of goods: 1263 PAINT, special provision 640D

· Maritime transport IMDG:



- IMDG Class: 3
- UN Number: 1263
- Label: 3
- Packaging group: II
- EMS Number: F-E,S-E
- Marine pollutant: No
- Proper shipping name: PAINT

· Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 3
- UN/ID Number: 1263
- Label: 3
- Packaging group: II
- Proper shipping name: PAINT

15 Regulations

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

(Contd. on page 7)

Printing date 06/03/2005

Reviewed on 12/21/2004

Trade name: 39854 Texture Coating

(Contd. of page 6)

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
	ACRYLIC RESIN
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)
78-93-3	butanone
1330-20-7	xylene
67-56-1	methanol
100-41-4	ethylbenzene

· **TSCA (Toxic Substances Control Act):**

108-88-3	toluene
14808-60-7	Quartz (SiO ₂)
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)
78-93-3	butanone
108-65-6	2-methoxy-1-methylethyl acetate
1333-86-4	Carbon black
111-76-2	2-butoxyethanol
1330-20-7	xylene
67-56-1	methanol
100-41-4	ethylbenzene

· **Proposition 65**

· **Chemicals known to cause cancer:**

14808-60-7	Quartz (SiO ₂)
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE
1333-86-4	Carbon black
1330-20-7	xylene

· **Chemicals known to cause reproductive toxicity:**

108-88-3	toluene
----------	---------

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

108-88-3	toluene	D
78-93-3	butanone	D
1330-20-7	xylene	D
100-41-4	ethylbenzene	D

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
14808-60-7	Quartz (SiO ₂)	1
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	3
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE	TRACE AMOUNTS OF 14808-60-7
1333-86-4	Carbon black	2B
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

(Contd. on page 8)

Printing date 06/03/2005

Reviewed on 12/21/2004

Trade name: 39854 Texture Coating

(Contd. of page 7)

· TLV (Threshold Limit Value established by ACGIH)		
108-88-3	toluene	A4
14808-60-7	Quartz (SiO ₂)	A2
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
1333-86-4	Carbon black	A4
1330-20-7	xylene	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
14808-60-7	Quartz (SiO ₂)	
1333-86-4	Carbon black	
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

Toxic

Highly flammable

· **Hazard-determining components of labelling:**

toluene

Quartz (SiO₂)

· **Risk phrases:**

May cause cancer by inhalation.

Highly flammable.

Harmful by inhalation.

Irritating to eyes, respiratory system and skin.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Harmful: possible risk of irreversible effects through inhalation.

Possible risk of harm to the unborn child.

Harmful: may cause lung damage if swallowed.

· **Safety phrases:**

Avoid exposure - obtain special instructions before use.

Keep locked up and out of the reach of children.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Wear suitable protective clothing and gloves.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** Environment protection department.

· **Contact:** Mr. George Wallace