



## SAFETY DATA SHEET

Revision date 08-Mar-2016

Version 6

Supersedes Date: 12-Feb-2016

### Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**Product identifier**

**Product Code** PBC38

**Product Name** LIMETIME PEARL

**Other means of identification**

No information available

**Recommended use of the chemical and restrictions on use**

Tint, colorant

**Details of the supplier of the safety data sheet**

See section 16 for more  
information

The Valspar Corporation  
PO Box 1461  
Minneapolis, MN 55440

**E-mail address** [msds@valspar.com](mailto:msds@valspar.com)

**Emergency telephone number**

United States of America 1-888-345-5732

American Samoa, Guam, Northern Mariana Islands, Puerto Rico, U.S. Virgin Islands 1-800-255-3924

### Section 2: HAZARDS IDENTIFICATION

**Classification**

|                                                    |            |
|----------------------------------------------------|------------|
| Acute toxicity - Inhalation (Dusts/Mists)          | Category 4 |
| Skin corrosion/irritation                          | Category 2 |
| Serious eye damage/eye irritation                  | Category 2 |
| Skin sensitization                                 | Category 1 |
| Carcinogenicity                                    | Category 2 |
| Reproductive toxicity                              | Category 2 |
| Specific target organ toxicity (single exposure)   | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 2 |
| Aspiration toxicity                                | Category 1 |
| Flammable liquids                                  | Category 3 |

**Product Code PBC38**

Page 1 / 10

AGHS - USA OSHA SDS

## Label elements



Signal word

**DANGER**

### **HAZARD STATEMENTS**

Flammable liquid and vapor  
Harmful if inhaled  
Causes skin irritation  
Causes serious eye irritation  
May cause an allergic skin reaction  
Suspected of causing cancer  
Suspected of damaging fertility or the unborn child  
May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways

### **PREVENTION**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

### **RESPONSE**

IF exposed or concerned: Get medical advice/attention.

#### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### **Skin**

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

#### **Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

#### **Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

#### **Fire**

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction.

### **STORAGE**

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

### **DISPOSAL**

Dispose of contents/containers in accordance with local regulations.

### **HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)**

Not applicable.

### **OTHER HAZARDS**

May be harmful in contact with skin.

### **UNKNOWN ACUTE TOXICITY**

0% of the mixture consists of ingredient(s) of unknown toxicity.

## **Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**Product Code PBC38**

Page 2 / 10

AGHS - USA OSHA SDS

| Chemical Name              | CAS No    | weight-%  |
|----------------------------|-----------|-----------|
| n-Butyl acetate            | 123-86-4  | 25 - 50   |
| Xylenes                    | 1330-20-7 | 10 - 25   |
| m-Xylene                   | 108-38-3  | 5 - 10    |
| Ethylbenzene               | 100-41-4  | 5 - 10    |
| p-Xylene                   | 106-42-3  | 1 - 3     |
| o-Xylene                   | 95-47-6   | 1 - 3     |
| Rutile (TiO <sub>2</sub> ) | 1317-80-2 | 1 - 3     |
| Toluene                    | 108-88-3  | 0.1 - 0.3 |
| Proprietary Additive       | UNKNOWN   | 0.1 - 0.3 |

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## Section 4: FIRST AID MEASURES

### First Aid Measures

#### **General advice**

IF exposed or concerned: Get medical advice/attention.

#### **Eye contact**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### **Skin Contact**

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

#### **Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

#### **Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

### Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

## Section 5: FIRE FIGHTING MEASURES

### Suitable extinguishing media

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

### Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact.

### Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

## Section 6: ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

### Personal precautions

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

### For emergency responders

Use personal protection recommended in Section 8.

### Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so.

### Methods and material for containment and cleaning up

#### Methods for containment

Prevent further leakage or spillage if safe to do so.

#### Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Take up mechanically, placing in appropriate containers for disposal. Pick up and transfer to properly labeled containers.

## Section 7: HANDLING AND STORAGE

### Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

#### General Hygiene Considerations

Avoid contact with skin, eyes or clothing. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

### Conditions for safe storage, including any incompatibilities

#### Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep tightly closed in a dry and cool place.

#### Incompatible materials

Strong oxidizing agents.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Limits

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

| Chemical Name               | ACGIH TLV                     | OSHA PEL                                   | NIOSH IDLH                                                                                                   |
|-----------------------------|-------------------------------|--------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| n-Butyl acetate<br>123-86-4 | STEL: 200 ppm<br>TWA: 150 ppm | TWA: 150 ppm<br>TWA: 710 mg/m <sup>3</sup> | IDLH: 1700 ppm<br>TWA: 150 ppm<br>TWA: 710 mg/m <sup>3</sup><br>STEL: 200 ppm<br>STEL: 950 mg/m <sup>3</sup> |
| Xylenes<br>1330-20-7        | STEL: 150 ppm<br>TWA: 100 ppm | TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup> |                                                                                                              |

|                                         |                               |                                            |                                                                                                             |
|-----------------------------------------|-------------------------------|--------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| m-Xylene<br>108-38-3                    | STEL: 150 ppm<br>TWA: 100 ppm | TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup> | IDLH: 900 ppm<br>TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>STEL: 150 ppm<br>STEL: 655 mg/m <sup>3</sup> |
| Ethylbenzene<br>100-41-4                | TWA: 20 ppm                   | TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup> | IDLH: 800 ppm<br>TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>STEL: 125 ppm<br>STEL: 545 mg/m <sup>3</sup> |
| p-Xylene<br>106-42-3                    | STEL: 150 ppm<br>TWA: 100 ppm | TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup> | IDLH: 900 ppm<br>TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>STEL: 150 ppm<br>STEL: 655 mg/m <sup>3</sup> |
| o-Xylene<br>95-47-6                     | STEL: 150 ppm<br>TWA: 100 ppm | TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup> | IDLH: 900 ppm<br>TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>STEL: 150 ppm<br>STEL: 655 mg/m <sup>3</sup> |
| Rutile (TiO <sub>2</sub> )<br>1317-80-2 | TWA: 10 mg/m <sup>3</sup>     | TWA: 15 mg/m <sup>3</sup> total dust       | IDLH: 5000 mg/m <sup>3</sup>                                                                                |
| Toluene<br>108-88-3                     | TWA: 20 ppm                   | TWA: 200 ppm<br>Ceiling: 300 ppm           | IDLH: 500 ppm<br>TWA: 100 ppm<br>TWA: 375 mg/m <sup>3</sup><br>STEL: 150 ppm<br>STEL: 560 mg/m <sup>3</sup> |

### **Appropriate engineering controls**

#### **Engineering Controls**

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

### **Individual protection measures, such as personal protective equipment**

#### **Eye/face protection**

Tight sealing safety goggles.

#### **Skin and body protection**

Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing.

#### **Hand Protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

#### **Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

#### **Thermal Protection**

No information available

## **Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

### **Information on basic physical and chemical properties**

|                       |                          |
|-----------------------|--------------------------|
| <b>Physical state</b> | liquid                   |
| <b>Appearance</b>     | No information available |
| <b>Odor</b>           | Solvent                  |
| <b>Color</b>          | metallic                 |
| <b>Odor Threshold</b> | No information available |

**Product Code PBC38**

Page 5 / 10

AGHS - USA OSHA SDS

|                               |                                  |
|-------------------------------|----------------------------------|
| pH value                      | No information available         |
| Melting point/freezing point  | No information available         |
| Boiling point / boiling range | No information available °C / °F |
| flash point                   | 27 °C / 81 °F                    |
| evaporation rate              | No information available         |
| Flammability (solid, gas)     | No information available         |
| Flammability Limit in Air     |                                  |
| Upper flammability limit:     | No information available         |
| Lower flammability limit:     | No information available         |
| Vapor Pressure                | No information available         |
| vapor density                 | No information available         |
| Density (lbs per US gallon)   | 7.94                             |
| specific gravity              | .95                              |
| Solubility(ies)               | No information available         |
| Partition coefficient         | No information available         |
| Autoignition temperature      | No information available         |
| Decomposition temperature     | No information available         |
| Kinematic viscosity           | No information available         |
| Dynamic viscosity             | No information available         |

#### Other information

### Section 10: STABILITY AND REACTIVITY

|                                    |                                        |
|------------------------------------|----------------------------------------|
| Reactivity                         | No information available.              |
| Chemical stability                 | Stable under normal conditions.        |
| Possibility of Hazardous Reactions | None under normal processing.          |
| Hazardous polymerization           | None under normal processing.          |
| Conditions to avoid                | Heat, flames and sparks.               |
| Incompatible materials             | Strong oxidizing agents.               |
| Hazardous Decomposition Products   | Carbon monoxide. Carbon dioxide (CO2). |

### Section 11: TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

##### **Eye contact**

Causes serious eye irritation

##### **Skin Contact**

Causes skin irritation

May cause an allergic skin reaction

##### **Ingestion**

May be fatal if swallowed and enters airways

##### **Inhalation**

Harmful if inhaled

May cause drowsiness or dizziness

#### Numerical measures of toxicity - Component Information

| Chemical Name               | Oral LD50             | Dermal LD50              | Inhalation LC50          |
|-----------------------------|-----------------------|--------------------------|--------------------------|
| n-Butyl acetate<br>123-86-4 | = 14.13 mg/kg ( Rat ) | > 17600 mg/kg ( Rabbit ) | = 390 ppm ( Rat ) 4 h    |
| Xylenes<br>1330-20-7        | = 3500 mg/kg ( Rat )  | > 4350 mg/kg ( Rabbit )  | = 29.08 mg/L ( Rat ) 4 h |
| m-Xylene<br>108-38-3        | = 5000 mg/kg ( Rat )  | -                        | -                        |
| Ethylbenzene<br>100-41-4    | = 3500 mg/kg ( Rat )  | = 15400 mg/kg ( Rabbit ) | = 17.2 mg/L ( Rat ) 4 h  |

**Product Code PBC38**

Page 6 / 10

AGHS - USA OSHA SDS

|                                 |                       |                          |                         |
|---------------------------------|-----------------------|--------------------------|-------------------------|
| p-Xylene<br>106-42-3            | = 4029 mg/kg ( Rat )  | -                        | = 4740 ppm ( Rat ) 4 h  |
| o-Xylene<br>95-47-6             | = 3608 mg/kg ( Rat )  | = 14100 mg/kg ( Rabbit ) | = 4330 ppm ( Rat ) 6 h  |
| Rutile (TiO2)<br>1317-80-2      | > 10000 mg/kg ( Rat ) | -                        | -                       |
| Toluene<br>108-88-3             | = 2600 mg/kg ( Rat )  | = 12000 mg/kg ( Rabbit ) | = 12.5 mg/L ( Rat ) 4 h |
| Proprietary Additive<br>UNKNOWN | -                     | -                        | -                       |

#### **Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (dermal)** 4485 Mg/kg

**ATEmix (inhalation-dust/mist)** 5 mg/l

**ATEmix (inhalation-vapor)** 37 mg/l

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

#### **Delayed and immediate effects as well as chronic effects from short and long-term exposure**

#### **Carcinogenicity**

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials.

| <b>Chemical Name</b>       | <b>ACGIH</b> | <b>IARC</b> | <b>NTP</b> | <b>OSHA</b> |
|----------------------------|--------------|-------------|------------|-------------|
| Ethylbenzene<br>100-41-4   | A3           | Group 2B    |            | X           |
| Rutile (TiO2)<br>1317-80-2 |              | Group 2B    |            | X           |

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen.

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

**Skin corrosion/irritation**

Causes skin irritation

**Serious eye damage/eye irritation**

Causes serious eye irritation

**Skin sensitization**

May cause an allergic skin reaction

**Respiratory sensitization**

Not applicable

**Germ cell mutagenicity**

Not applicable

**Carcinogenicity**

Suspected of causing cancer

**Reproductive Toxicity**

Suspected of damaging fertility or the unborn child

**Specific target organ toxicity (single exposure)**

May cause drowsiness or dizziness

**Specific target organ toxicity (repeated exposure)**

May cause damage to organs through prolonged or repeated exposure

**Aspiration hazard**

Not applicable

## **Section 12: ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

Environmental precautions

Prevent product from entering drains.

#### **Persistence and degradability**

No information available

#### **Bioaccumulation**

No information available

#### **Mobility**

No information available

#### **Other adverse effects**

No information available

**Product Code PBC38**

Page 7 / 10

AGHS - USA OSHA SDS

## Section 13: DISPOSAL CONSIDERATIONS

### Waste treatment methods

|                               |                                                                                                                                |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| <b>Disposal of wastes</b>     | Disposal should be in accordance with applicable regional, national and local laws and regulations.                            |
| <b>Contaminated packaging</b> | Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned. |

## Section 14: TRANSPORT INFORMATION

|                                                                                      | <u>DOT</u>                             | <u>IMDG</u>            | <u>IATA</u>            |
|--------------------------------------------------------------------------------------|----------------------------------------|------------------------|------------------------|
| <b>14.1 UN/ID no</b>                                                                 | UN1263                                 | UN1263                 | UN1263                 |
| <b>14.2 Proper shipping name</b>                                                     | Paint related material                 | Paint related material | Paint related material |
| <b>14.3 Hazard Class</b>                                                             | 3                                      | 3                      | 3                      |
| <b>14.4 Packing Group</b>                                                            | III                                    | III                    | III                    |
| <b>14.5 Environmental hazard</b>                                                     | Not applicable                         |                        |                        |
| <b>14.6 Special Provisions</b>                                                       | B1, B52, IB3, T2, TP1, TP29            | 163, 223, 955          | A3, A72                |
|                                                                                      | <b>Emergency Response Guide Number</b> | <b>EmS-No</b>          |                        |
|                                                                                      | 128                                    | F-E, S-E               |                        |
| <b>14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b> | No information available               |                        |                        |

*The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.*

## Section 15: REGULATORY INFORMATION

### International Inventories

|                                                                                 |                                                   |
|---------------------------------------------------------------------------------|---------------------------------------------------|
| <b>TSCA</b> - United States Toxic Substances Control Act Section 8(b) Inventory | All components are listed or exempt from listing. |
| <b>DSL</b> - Canadian Domestic Substances List                                  | All components are listed or exempt from listing. |

### US Federal Regulations

| Chemical Name                      | SARA 313 - Threshold Values % | Hazardous air pollutants (HAPs) content |
|------------------------------------|-------------------------------|-----------------------------------------|
| Xylenes<br>1330-20-7<br>10 - 25    | 1                             | Present                                 |
| m-Xylene<br>108-38-3<br>5 - 10     | 1                             | Present                                 |
| Ethylbenzene<br>100-41-4<br>5 - 10 | 0.1                           | Present                                 |
| p-Xylene<br>106-42-3<br>1 - 3      | 1                             | Present                                 |
| o-Xylene<br>95-47-6<br>1 - 3       | 1                             | Present                                 |
| Toluene<br>108-88-3<br>0.1 - 0.3   | 1                             | Present                                 |

### SARA 311/312 Hazard Categories

|                       |     |
|-----------------------|-----|
| Acute health hazard   | Yes |
| Chronic Health Hazard | Yes |
| Fire hazard           | Yes |

**Product Code PBC38**

Page 8 / 10

AGHS - USA OSHA SDS



**Sudden release of pressure hazard**  
**Reactive Hazard**

No  
 Yes

| Chemical Name               | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|-----------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| n-Butyl acetate<br>123-86-4 | 5000 lb                     |                        |                           | X                          |
| Xylenes<br>1330-20-7        | 100 lb                      |                        |                           | X                          |
| m-Xylene<br>108-38-3        | 100 lb                      |                        |                           | X                          |
| Ethylbenzene<br>100-41-4    | 1000 lb                     | X                      | X                         | X                          |
| p-Xylene<br>106-42-3        | 100 lb                      |                        |                           | X                          |
| o-Xylene<br>95-47-6         | 100 lb                      |                        |                           | X                          |
| Toluene<br>108-88-3         | 1000 lb                     | X                      | X                         | X                          |

| Chemical Name               | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ)                   |
|-----------------------------|--------------------------|----------------|--------------------------------------------|
| n-Butyl acetate<br>123-86-4 | 5000 lb                  |                | RQ 5000 lb final RQ<br>RQ 2270 kg final RQ |
| Xylenes<br>1330-20-7        | 100 lb                   |                | RQ 100 lb final RQ<br>RQ 45.4 kg final RQ  |
| m-Xylene<br>108-38-3        | 1000 lb                  |                | RQ 1000 lb final RQ<br>RQ 454 kg final RQ  |
| Ethylbenzene<br>100-41-4    | 1000 lb                  |                | RQ 1000 lb final RQ<br>RQ 454 kg final RQ  |
| p-Xylene<br>106-42-3        | 100 lb                   |                | RQ 100 lb final RQ<br>RQ 45.4 kg final RQ  |
| o-Xylene<br>95-47-6         | 1000 lb                  |                | RQ 1000 lb final RQ<br>RQ 454 kg final RQ  |
| Toluene<br>108-88-3         | 1000 lb                  |                | RQ 1000 lb final RQ<br>RQ 454 kg final RQ  |

**US State Regulations**

**Rule 66 status of product**

Photochemically reactive.

**California Proposition 65**

WARNING! This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

**U.S. EPA Label information**

**EPA Pesticide registration number** Not applicable

**U.S. State Right-to-Know Regulations**

|                                                        |
|--------------------------------------------------------|
| Chemical Name                                          |
| n-Butyl acetate<br>123-86-4                            |
| Xylenes<br>1330-20-7                                   |
| Proprietary Non-Hazardous Ingredient - Proprietary CAS |
| Proprietary Non-Hazardous Ingredient - Proprietary CAS |
| m-Xylene<br>108-38-3                                   |
| Proprietary Non-Hazardous Ingredient - Proprietary CAS |

|                                         |
|-----------------------------------------|
| Ethylbenzene<br>100-41-4                |
| o-Xylene<br>95-47-6                     |
| p-Xylene<br>106-42-3                    |
| Rutile (TiO <sub>2</sub> )<br>1317-80-2 |
| C.I. Pigment Green 36<br>14302-13-7     |
| Proprietary Inert                       |
| Toluene<br>108-88-3                     |

## Section 16: OTHER INFORMATION

### HMIS

**Health hazards** 3\*

\* = Chronic Health Hazard

**Flammability** 3

**Physical hazards** 1

**Personal Protection** X

### **Supplier Address**

Valspar Coatings  
701 Shiloh Rd.  
Garland, TX 75042  
972-276-5181

**Prepared By** Product Stewardship

**Revision date** 08-Mar-2016

**Revision Note** No information available

### Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. **UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.**

**End of Safety Data Sheet**