

## 1 Identification

- **Product identifier**
- **Trade name:** *40477 Heavy Bodied White Seam Sealer*
- **Article number:** 40477
- **Application of the substance / the mixture** Sealant
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SEM Products Inc.  
1685 Overview Drive  
Rock Hill, SC 29730  
803 207 8225
- **Information department:**  
cust\_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07



GHS08

- **Signal word** Warning

- **Hazard-determining components of labeling:**

bisphenolA(chloro)oxirane polymer

Mercaptan Terminated Polymer NJTS 800938 5952

titanium dioxide

2,4,6-tris(dimethylaminomethyl)phenol

- **Hazard statements**

H302 Harmful if swallowed.

(Contd. on page 2)

**Trade name: 40477 Heavy Bodied White Seam Sealer**

(Contd. of page 1)

- H315 Causes skin irritation.*
- H319 Causes serious eye irritation.*
- H317 May cause an allergic skin reaction.*
- H351 Suspected of causing cancer.*
- H335 May cause respiratory irritation.*

· **Precautionary statements**

- P261 Avoid breathing dust/fume/gas/mist/vapors/spray*
- P280 Wear protective gloves.*
- P280 Wear eye protection / face protection.*
- P264 Wash thoroughly after handling.*
- P270 Do not eat, drink or smoke when using this product.*
- P271 Use only outdoors or in a well-ventilated area.*
- P272 Contaminated work clothing must not be allowed out of the workplace.*
- P201 Obtain special instructions before use.*
- P202 Do not handle until all safety precautions have been read and understood.*
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
- P321 Specific treatment (see on this label).*
- P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.*
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
- P363 Wash contaminated clothing before reuse.*
- P308+P313 IF exposed or concerned: Get medical advice/attention.*
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.*
- P337+P313 If eye irritation persists: Get medical advice/attention.*
- P330 Rinse mouth.*
- P302+P352 IF ON SKIN: Wash with plenty of water.*
- P362+P364 Take off contaminated clothing and wash it before reuse.*
- P405 Store locked up.*
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.*
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.



Trade name: 40477 Heavy Bodied White Seam Sealer

(Contd. of page 2)

### 3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:**  
Mixture consisting of the following components.  
Weight percentages

· **Dangerous components:**

	Mercaptan Terminated Polymer NJTS 800938 5952	30 - 40%
25068-38-6	bisphenolA(chloro)oxirane polymer	13 - 30%
13463-67-7	titanium dioxide	7 - 10%
67762-90-7	FUMED SILICA	5 - 7%
26142-30-3	POLYMER OF EPICHLOROHYDRIN-POLYGLYCOL	5 - 7%
25085-99-8	BISPHENOL A EPOXY RESIN	5 - 7%
68909-14-8	Elastomer modified diglycidal ether	1.5 - 5%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	1.5 - 5%
17557-23-2	1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	1-1.5%
74398-71-3	CASTOR OIL GLYCIDAL ETHER	≤1%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

USA

(Contd. on page 4)



Trade name: 40477 Heavy Bodied White Seam Sealer

(Contd. of page 3)

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.
- **Breathing equipment:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

Trade name: 40477 Heavy Bodied White Seam Sealer

(Contd. of page 4)

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Liquid  
**Color:** According to product specification

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** 201 °C

· **Flash point:** 257 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:**

**Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.  
In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

**Lower:** Not determined.  
**Upper:** Not determined.

(Contd. on page 6)



Trade name: 40477 Heavy Bodied White Seam Sealer

(Contd. of page 5)

· Vapor pressure:	Not determined.
· Density at 20 °C:	1.41243 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
Solids content:	99.6 %
· Other information	No further relevant information available.

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant
- **Carcinogenic categories**

· <b>IARC (International Agency for Research on Cancer)</b>		
13463-67-7	titanium dioxide	2B
7631-86-9	silicon dioxide, chemically prepared	3
1333-86-4	Carbon black	2B
64-17-5	ethanol	1

(Contd. on page 7)



Trade name: 40477 Heavy Bodied White Seam Sealer

(Contd. of page 6)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Generally not hazardous for water
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.


**14 Transport information**

- |                                  |   |
|----------------------------------|---|
| · <b>UN-Number</b>               |   |
| · <b>DOT, ADR, ADN, IATA</b>     | Void  |
| · <b>IMDG</b>                    | UN3082  |
|                                  |   |
| · <b>UN proper shipping name</b> |   |
| · <b>DOT, ADR, ADN, IATA</b>     | Void  |
| · <b>IMDG</b>                    | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. |

(Contd. on page 8)

Trade name: 40477 Heavy Bodied White Seam Sealer

(Contd. of page 7)

· <b>Transport hazard class(es)</b>	
· <b>DOT, ADR, ADN, IATA</b>	
· <b>Class</b>	Void
<hr/>	
· <b>IMDG</b>	
	
· <b>Class</b>	9 Miscellaneous dangerous substances and articles
· <b>Label</b>	9
· <b>Packing group</b>	
· <b>DOT, ADR, IATA</b>	Void
· <b>IMDG</b>	III
· <b>Environmental hazards:</b>	Product contains environmentally hazardous substances: bisphenolA(chloro)oxirane polymer
· <b>Marine pollutant:</b>	Yes Symbol (fish and tree)
· <b>Special precautions for user</b>	Not applicable.
· <b>EMS Number:</b>	F-A,S-F
· <b>Stowage Category</b>	A
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Remarks</b>	NOT REGULATED
<hr/>	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	Void

**15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture  
· Sara

· <b>Section 355 (extremely hazardous substances):</b>	None of the ingredient is listed.
· <b>Section 313 (Specific toxic chemical listings):</b>	
68909-14-8	Elastomer modified diglycidal ether
107-21-1	ethanediol
67-56-1	methanol

(Contd. on page 9)





Trade name: 40477 Heavy Bodied White Seam Sealer

(Contd. of page 8)

· TSCA (Toxic Substances Control Act):	
25068-38-6	bisphenolA(chloro)oxirane polymer
13463-67-7	titanium dioxide
67762-90-7	FUMED SILICA
26142-30-3	POLYMER OF EPICHLOROHYDRIN-POLYGLYCOL
25085-99-8	BISPHENOL A EPOXY RESIN
68909-14-8	Elastomer modified diglycidal ether
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol
17557-23-2	1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane
7631-86-9	silicon dioxide, chemically prepared
74398-71-3	CASTOR OIL GLYCIDAL ETHER
21645-51-2	aluminium hydroxide
107-21-1	ethanediol
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane
919-30-2	3-aminopropyltriethoxysilane
1333-86-4	Carbon black

· Proposition 65

· Chemicals known to cause cancer:	
25068-38-6	bisphenolA(chloro)oxirane polymer
13463-67-7	titanium dioxide
25085-99-8	BISPHENOL A EPOXY RESIN
74398-71-3	CASTOR OIL GLYCIDAL ETHER
107-21-1	ethanediol
1333-86-4	Carbon black

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

107-21-1	ethanediol
67-56-1	methanol
64-17-5	ethanol

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

13463-67-7	titanium dioxide	A4
107-21-1	ethanediol	A4
1333-86-4	Carbon black	A4
64-17-5	ethanol	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7	titanium dioxide
------------	------------------

(Contd. on page 10)

Trade name: 40477 Heavy Bodied White Seam Sealer

(Contd. of page 9)

1333-86-4	Carbon black
67-56-1	methanol

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

bisphenolA(chloro)oxirane polymer  
Mercaptan Terminated Polymer NJTS 800938 5952  
titanium dioxide  
2,4,6-tris(dimethylaminomethyl)phenol

· **Hazard statements**

H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H335 May cause respiratory irritation.

· **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapors/spray  
P280 Wear protective gloves.  
P280 Wear eye protection / face protection.  
P264 Wash thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321 Specific treatment (see on this label).  
P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P363 Wash contaminated clothing before reuse.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P330 Rinse mouth.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P405 Store locked up.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 11)



**Trade name: 40477 Heavy Bodied White Seam Sealer**

(Contd. of page 10)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver (sgaver@semproducts.com)

· **Date of preparation / last revision** 06/01/2016 / 5

· **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*NIOSH: National Institute for Occupational Safety*

*OSHA: Occupational Safety & Health*

*TLV: Threshold Limit Value*

*PEL: Permissible Exposure Limit*

*REL: Recommended Exposure Limit*

*Acute Tox. 4: Acute toxicity – Category 4*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A*

*Skin Sens. 1: Skin sensitisation – Category 1*

*Carc. 2: Carcinogenicity – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

· **\* Data compared to the previous version altered.**