



RUBBERIZED UNDERCOATING

TECHNICAL DATA SHEET

Description

39523 RUBBERIZED UNDERCOATING and **4052() LOW VOC RUBBERIZED UNDERCOATING** are paintable, fast-drying, asphalt free coatings for rust proofing, sound deadening, chip resistance and corrosion protection. **4052()** is less than 40% VOC.

Features

- Asphalt free
- Paintable
- Sound-deadening
- Fast-drying
- Chip resistant
- Corrosion protection

Typical Properties

Container	39523 & 40523 24 oz. aerosol 40524 quart bottle	
Color	Black	
	<u>Regulatory</u>	<u>Actual</u>
VOC 39523	4.80 #/gl (576 g/l)	4.80 #/gl (576 g/l)
VOC 40523	3.86 #/gl (463 g/l)	2.79 #/gl (335 g/l)
VOC 40524	3.56 #/gl (428 g/l)	2.65 #/gl (318 g/l)
Paintable	Yes	

Handling and Application

PREPARATION: Clean surface with **3837() SEM SOLVE**. Remove any loose paint, rust, oil and grease. Blow off and clean again with **3837()**.



APPLICATION:



Aerosol:

Distance: 6-8"
Coats: 2-3 medium wet
Flash time: 3-5 minutes

NOTE: If clogging develops, remove spray button with a twisting motion and clean with material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.

NOTE: After each use, turn can upside down and spray several seconds to clear spray tip.



Bulk:

Attach **40524** to **71101 ECONOMY COATING GUN**. Using 35-40 psi, apply 2-3 medium coats allowing 3-5 minutes flash time between coats. Clean gun immediately after use with solvent compliant in your area.

NOTE: Final texture, flash times, and dry times are affected by gun distance, air pressure, temperature, and humidity.

STORAGE:

39523 RUBBERIZED UNDERCOATING and **4052() LOW VOC RUBBERIZED UNDERCOATING** should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **39523** and **4052()** is 3 years when stored under normal conditions.

TECHNICAL CONSULTATION SERVICE

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.

SEM Products, Inc.
1685 Overview Dr. Rock Hill SC 29730
Tel: 800/ 831-1122
www.semproducts.com