

**ADVANTAGE REFINISH PRODUCTS**  
**TECHNICAL DATA INFORMATION**  
**DATED: OCTOBER 2018**

**PRODUCT NUMBER DESCRIPTION**

#3524 - Super View Guide Coat Aerosol (15 fl. oz )

**DESCRIPTION:**

***#3524 Super View Guide Coat allows you to achieve a perfect repair every time.***

It provides a visual guide when sanding over primer, body fillers, and glazing putties. Detect low spots, scratches or other minor imperfections in the repair. This ultra thin coating wets the surface evenly, dries fast, and will not clog sandpaper.

**SUGGESTED USES:**

Automotive body panels  
Fiberglass  
Wood

**DIRECTIONS:**

The sprayhead provides a horizontal and vertical fan spray that can be changed by turning the nozzle clockwise or counter clockwise.

1. Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Spray surface with steady even strokes at a distance of 8 to 10 inches (20cm to 25cm). Turning the orifice of the sprayhead allows for vertical or horizontal spray patterns. Several light coats give a better finish than one heavy coat. Dries to touch in 20 minutes.
4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. Do not stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

**Dry Time\*:**

To touch 5 minutes

To Topcoat 15 minutes

\*At 72F, 50% humidity, 0.3 mil thickness

**Gloss\*:** Flat, <15

\*as measured on a 60 degree gloss meter

## **PROPERTIES:**

Coverage Up to 15 square feet  
Cleanup Paint/lacquer thinner  
Flammability Extremely Flammable  
Flash point -4F  
Specific Gravity 0.85  
MIR Value: 0.82, does not exceed 0.95  
Solids Content 7%  
HAPs content 9%  
Storage Temperature 40-100F  
Application Temperature 50-90F  
Abrasion Resistance Fair  
Heat Resistance 250F continuous  
Resin System Acrylic lacquer  
Shelf life Guaranteed for 2 years

## **SAFETY INFORMATION - FOR INDUSTRY USE ONLY**

DANGER Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Prevention: Pressurized container: do not pierce or burn, even after use. Use only with adequate ventilation. Do not breathe dust/vapors/spray mist. Avoid contact with eyes/skin/clothing. Wear protective gloves/clothing/glasses. Keep away from heat/sparks/open flames/hot surfaces. Do not eat/drink/smoke when using this product. Do not spray on naked flame or other ignition sources. Response: In case of fire, use extinguishing powder or water spray. Immediately contact a doctor or POISON CONTROL CENTER if you feel unwell. If medical attention is needed, have product label at hand. IF IN EYES: Rinse with water for several minutes. Remove contact lenses if present. If eye irritation persists seek medical attention. IF SWALLOWED: Rinse mouth with water. Do not induce vomiting. IF INHALED: Remove to fresh air. IF ON SKIN: Wash thoroughly with water. Remove all contaminated clothing. Storage: Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Disposal: Dispose of product in accordance with local/regional/national/international regulations. Additional Precaution Statements: Vapors may ignite explosively and cause a flash fire. Prevent buildup of vapors by opening windows and doors to achieve cross ventilation. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately inhaling the contents may be harmful or fatal. In cases where short and/or long term overexposure conditions exist, a charcoal filter respirator should be worn. Follow respirator manufacturer's directions for use. **KEEP OUT OF REACH OF CHILDREN • Read Safety Data Sheet Before Use**

**Made in U.S.A (Manufactured for - ABI/Autobody Brands International a  
division of IAMG/International Autobody Marketing Group)  
1505 N. Hayden Road - Suite 111 Scottsdale, AZ 85257 - 1-87-REFINISH  
[www.advantagerefinish.com](http://www.advantagerefinish.com)**