

### Product Data Sheet

A fast drying, heavy bodied rubber and asphalt coating for sealing, sound deadening, hiding repairs and rustproofing. Provides excellent adhesion to bare or painted metals and plastics. also works as a sealant for house gutters, fence posts and trees after pruning.

#### PRODUCT

22104	850 ml (28.7 fl oz)	Black
22106	3.78 L (1 U.S. Gallon)	Black
22108	18.9 L (5 U.S. Gallons)	Black

#### SURFACE PREPARATION:



All substrates must be degreased and sanded. Surface must be free of rust, wax, silicone, grease, dirt and other contaminants. Clean metal with 13520 Wax and Grease Remover. Clean plastic surfaces with 19040 Plastic Parts Cleaner. For best results, use when temperature of the can and surface is between 21°C and 24°C (70°F and 75°F).

#### APPLICATION:



Using a 26172 Siphon Gun at 50 to 80 psi, adjust air pressure and spray approximately 25-30 cm (10 to 12") from surface. Distance and pressure at the gun will determine texture.

#### DRYING TIME

Approximately 2-3 hours



#### CLEAN UP



Clean equipment immediately after use with 19002 General Purpose Adhesive Cleaner. Clean all spray equipment immediately after use as activated paints will harden in equipment.

#### TECHNICAL DATA:

APPEARANCE: Black

VISCOSITY: 5600 cps #4 Spindle @ 20 rpm

V.O.C. CONTENT: Regulatory 3.6 lbs/gal 430 g/l Actual: 3.24 lbs/gal 388 g/l



# Paintable Rubberized Undercoat 22104, 22106, 22108

## Product Data Sheet

### **PRECAUTIONARY INFORMATION**

Refer to product label and Safety Data Sheet for health and safety information before using this product.

### **SAFETY CONSIDERATION**

Safety Data Sheets are available at [www.proformproducts.com](http://www.proformproducts.com) or upon request at [info@proformproducts.com](mailto:info@proformproducts.com). These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

### **TECHNICAL INFORMATION:**

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

### **PRODUCT USE:**

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

### **WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY**

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss.